



S.E.A.

OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear
FIBERGLASS + RESIN

MATERIAL SAFETY DATA SHEET

ACM BLUE GLASS FIBER E-WOVEN CLOTH

SECTION 1 – CHEMICAL PRODUCT IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

Product name: **ACM BLUE GLASS FIBER E-WOVEN CLOTH**

Industrial application: industrial

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients of Products

CAS No. :

Fiber glass: 65997-17-3

Size: N/A

SECTION 3 – HAZARDS IDENTIFICATION

Classification of Hazards :

No information available.

Routes of Entry :

Ingestion, inhalation, skin and eye contact

Health Effects :

Ingestion: Ingestion of the material is unlikely. However, ingestion of the material may cause gastrointestinal disturbance.

Inhalation: Breathing fiberglass dusts and particulates may cause irritation of the nose, throat and respiratory tract.

Skin contact: Fiberglass dusts and particulates may cause temporary irritation.

Eye contact: Fiberglass dusts and particulates may cause temporary irritation to the eyes.

Environmental Effects :

Long-term exposure to fiberglass environment may cause temporary effects.

Inflammation and Explosion Hazards :

No information available.

LUZON:

REGIONAL OFFICE
TAGUIG

1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

VISAYAS:

HEADQUARTERS
CEBU

2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO

Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph



S.E.A.

OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear
FIBERGLASS + RESIN

SECTION 4 – FIRST-AID MEASURES

Skin Contact:

If irritation occurs to the skin, rinse with soap and water. Make sure to refrain from rinsing with warm water since warm water will make the skin pores open to allow fiberglass to penetrate more deeply. If fiberglass penetrates the skin, use a wash cloth to help pull out the fiberglass. To avoid further irritation, do not rub or scratch affected skin. If irritation persists, get medical help. Make sure to refrain from using compressed air to remove fiberglass from the skin.

Eye Contact:

Immediately flush eyes with clean water for at least 15 minutes. If irritation persists, get medical help.

Inhalation:

If inhaled, immediately remove the affected person to fresh air. If irritation persists, get medical help.

Ingestion:

Normally, ingestion of this material is unlikely. If it does occur, watch the person for several days to make sure that gastrointestinal disturbance does not occur. Do not let the person vomit unless required by medical personnel. If disturbance persists, get medical help.

SECTION 5 – FIRE-FIGHTING MEASURES

Flammability Classification :

Non-flammable. But the size and packing material may burn.

Hazardous Combustion Products :

Primary combustion products are carbon monoxide, hydrogen, carbon dioxide and water. Other undetermined compounds can be released in small quantities.

Fire-Fighting Methods :

Use dry chemical, foam, carbon dioxide and water as extinguishing media.

Fire-Fighting Instructions:

Fire fighters must use self-contained breathing apparatus and wear full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

In case of release to land, the material should be scooped up as waste and put into a special container and stored in a designated area. In case of release of water, the material will sink and disperse along the bottom of waterways or ponds and cannot be easily removed after it is waterborne. However, the material is non-hazardous in water.

LUZON:

REGIONAL OFFICE
TAGUIG

1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

VISAYAS:

HEADQUARTERS
CEBU

2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO

Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph



SECTION 7 – HANDLING AND STORAGE

Handling :

Try to prevent the packing material from be damaged and keep the product inside the packing material to minimize the generation of dusts. Maintain a clean work environment and avoid generation of fiberglass fragments from improper handling.

Storage :

Keep product in its packaging until use to minimize potential dust generation.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Highest Permissible Concentration :

National and international hygiene standards are as follows :

| Component | Permissible Exposure Limit of OSHA (8-hr Average Weight) | Permissible Exposure Limit of ACGIH (8 hr Average Weight) |
|----------------------------|--|---|
| Total Dust | 15 mg/m ³ | 10 mg/m ³ |
| Respirable particulates | 5 mg/m ³ | 3 mg/m ³ |
| Respirable Fibre | / | 1 fibre/ml |

Engineering Control :

Production areas are closed off and a required relative humidity is maintained.

Respiratory Protection :

Wear a suitable mask when working in an environment where dust concentration is high.

Eye Protection :

Wear safety glasses and face shield.

Body Protection :

Normal loose working clothing (long-sleeved shirts and long pants) is recommended. Skin irritation occurs primarily at the contact areas such as around the neck and waist.

Hand Protection

Wear gloves. Skin irritation occurs primarily at the contact areas such as wrists and between the fingers.

LUZON:

REGIONAL OFFICE
TAGUIG
1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

VISAYAS:

HEADQUARTERS
CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO
Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph



S.E.A.

OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear
FIBERGLASS + RESIN

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Product Appearance and Properties:

White or off-white solid ; No odor.

PH Value :

Not applicable.

Melting Point :

>800°C.

Boiling Point :

Not applicable.

Relative Density :

2.6 Times that of water.

Relative Vapor Density :

Not applicable

Product Use :

Fiberglass is an inorganic nonmetal material and is used as Plastics reinforcement and acoustical insulation.

Flash Point :

Not applicable

Ignition Temperature :

Not applicable

Explosion Upper Limit :

Not applicable

Explosion Lower Limit :

Not applicable

Solubility (in Water):

Insoluble

SECTION 10 – STABILITY AND REACTIVITY

Stability:

This is a Stable material.

Materials to Avoid :

None

Conditions to avoid :

None

Hazardous Polymerization

Will not occur

SECTION 11 – TOXICOLOGICAL INFORMATION

Acute Toxicity :

None

Irritability :

Fiberglass dusts may cause irritation to skin and eye. Ingestion of fiberglass may cause irritation to the throat, stomach and gastrointestinal tract. Inhalation may cause coughing, sneezing and nose and throat irritation. Experience indicates that inhalation of a large amount of fiberglass may cause difficulty in breathing, congestion and chest tightness.

LUZON:

REGIONAL OFFICE
TAGUIG

1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

VISAYAS:

HEADQUARTERS
CEBU

2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO

Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph



S.E.A.
OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear
FIBERGLASS + RESIN

Carcinogenicity :

The International Agency for Research on Cancer (IARC), agency of the World Health Organization (WHO), has determined that fiberglass is a non-carcinogenic material because the evidence is inadequate to prove that fiberglass can cause humans and experimental animals to develop cancer.

SECTION 12 – ECOLOGICAL INFORMATION

No data available for this product. Fiberglass products are not listed as a material harmful to animals, plants and fish.

SECTION 13 – DISPOSAL CONSIDERATIONS

RCRA Hazard class :

Non-hazardous

Disposal Instructions :

Dispose waste material according to local environmental regulations.

SECTION 14 – TRANSPORT INFORMATION

Classification and Code of Hazards:

None.

UN Code :

None.

Packing Mark:

None.

Packing Category:

None.

Packing Method :

None.

Transport Instructions :

Rolling and moisture should be avoided in transit.

LUZON:

REGIONAL OFFICE
TAGUIG
1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel. #: (02) 506-8519 ; 837-0710
837-0708

VISAYAS:

HEADQUARTERS
CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel. #: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO
Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph



S.E.A.

OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear
FIBERGLASS + RESIN

SECTION 15 – REGULATORY INFORMATION

SARA title :

Hazard categories :

Acute health: Yes

Chronic health: No

Fire hazard: No

Pressure hazard: No

Reactivity hazard : No

Reportable ingredients :

Sec.302/304 : None

Sec.313 : None

Clean Air Act :

No ingredient is listed.

WHMIS (Canada) Status :

No controlled.

WHMIS classification(s):

None.

SECTION 16 – OTHER INFORMATION

Preparation Date :

Oct. 2018

Prepared by :

Standardization and Measurement Dept.

Data Verified by :

Quality Dept.

Modification Information :

Second Version

The data and information contained in this Material Safety Data Sheet is provided to the best of our knowledge and ability on existing hazards, properties and handling of this product as recommended. It is recommended that the user tests the product according to its purpose. The user is responsible for the proper, safe and lawful use of this product. The information contained in this MSDS is subject to change without further notice. © 20

LUZON:

REGIONAL OFFICE
TAGUIG
1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

VISAYAS:

HEADQUARTERS
CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO
Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph



S.E.A.

OLYMPUS
Marketing, Inc.

www.olympus.com.ph

Poly Klear
FIBERGLASS + RESIN

TECHNICAL DATA SHEET

MATERIAL NAME: ACM BLUE GLASS FIBER E-WOVEN CLOTH

Woven cloth is a fabric made by interweaving rovings and is mainly used for hand lay-up process for large, high-strength FRP products such as boats, railroad carriages, storage tanks and architectural structures, etc. The roving size system of woven roving is silane and specification range 30-800g/m², width can be from 10-320cm, compatibility with polyester, vinyl ester and epoxy resin.

PROPERTIES

1. silane coupling
2. Fast wet-out rate
3. High mechanical strength
4. Good moldability

TECHNICAL CHARACTERISTICS

| Product code | Area weight (g/m ²) <i>ISO3374</i> | Warp density ends/cm <i>ISO4602</i> Yarn tex g/km <i>ISO1889</i> | Weft density Ends/cm <i>ISO4602</i> Yarn tex g/km <i>ISO1889</i> | Moisture (%) <i>ISO3344</i> | Loss Ignition % <i>ISO1887</i> |
|--------------|---|--|--|-----------------------------------|--------------------------------------|
| EWC200 | 200+/-10% | 8+/-0.5 132 | 7+/-0.5 132 | ≤0.15 | 0.4-0.8 |

PACKAGE

EWC is wound onto a paper core and then wrapped up with plastic film then put into cartons. Rolls can be load into container directly or on pallet.

STORAGE

Unless otherwise specified, fiberglass products should be stored in a dry, cool and rain-proof area. It is recommended that the room temperature and humidity should be always maintained at 35%-65% respectively.

LUZON:

REGIONAL OFFICE
TAGUIG
1st Avenue, Sta. Maria Industrial Subd,
Bagumbayan, Taguig City
Tel.#: (02) 506-8519 ; 837-0710
837-0708

VISAYAS:

HEADQUARTERS
CEBU
2F SEA Olympus Building, AC Cortes Ave.
Trunkline #: (032) 421-7777
Tel.#: (032) 346-7137 ; 421-7800 to 06
421-7817 to 18 ; 421-7823
Fax #: (032) 421-7789 ; 346-1817

MINDANAO:

REGIONAL OFFICE
DAVAO
Unit A16 J.King Warehouse Complex
Km.3 Maa Road, Davao City 8000
Telefax #: (082) 244-1206 ; 302-2711

✉ inquiry@olympus.com.ph